



#### **Ultra Safe**

Intelligent fire extinguishing system, react within 5 seconds



#### No Black Out

Maximum discharge current: 200A, simultaneously supplying power to multiple loads



## **Flexible Expansion**

Up to 50 units in parallel, 14.3kWh--716.8kWh capacity



# **Easy Installation**

60% less volume, 25% less weight. easy to move by one person with wheels



# Long-term Reliability

LFP cells, long cycles, 10 years warranty



### **Smart Management**

Real-time system monitoring, remote control, OTA updates

Model	PowerBrick
Battery Type	LiFePO <sub>4</sub>
Nominal Battery Energy	14.336kWh
Nominal Voltage/Capacity	51.2V/280Ah
Recommended Charge/Discharge Current	140A (0.5C)
Max. Charge Current	200A
Max. Discharge Current	200A
Peak Discharge Current	300A (2mins, 25°C)
Depth of Discharge	95%
Communication	CAN/RS485
Cycle Life[1]	≥8000 cycles / 10 Years
Protection Level	IP20
Net Weight	114Kg
Dimension[W/D/H]	435/233/857mm (No wall -mounted bracket)
Regulating wheel (4pcs)	1kg, 80/80/80 (optional)
Top cover	2kg, 422/232/60 (optional)
Maximum Parallel Modules	50
Charging Temp. Range	0°C~55°C/-20°C~55°C (optional)
Discharging Temp. Range	-20~55°C
WIFI Module	Built-in WIFI module; APP OTA function
Fire Protection System	Built-in aerosol fire extinguisher
Certification & Safety Standard	UN38.3/CE-EMC/IEC62619
Compatible Inverters	SMA/Victron energy/Ingeteam/Solis/GoodWe/ Growatt/Solplanet/Luxpower/DEYE/Apsystem etc.

<sup>\*</sup> Test conditions: 0.2C Charging & Discharging. @25°C, 90% DOD

